



**MATERIAL SAFETY DATA SHEET
 MAY BE USED TO COMPLY WITH OSHA'S HAZARD
 COMMUNICATION STANDARD 29 CFR 1910, 1200.
 STANDARD MUST BE CONSULTED FOR SPECIFIC REQUIREMENTS.**

COMPANY: TURRET PUNCH COMPANY, INC.

MATERIAL: APPLIES TO ALL POLYURETHANES

SECTION 1: CHEMICAL PRODUCT / COMPANY IDENTIFICATION

MATERIAL IDENTIFICATION URETHANE

FLAMABILITY OF URETHANE IS A MINIMUM OF 600F

THIS MATERIAL WILL START TO MELT AT 450F BUT WILL SELF EXTINGUISH IF FLAME SOURCE IS REMOVED.

COMPANY IDENTIFICATION / MAILING ADDRESS:

**7780 EDISON AVE
 FONTANA, CA 92336**

DATE PREPARED:

9/05/2011

COMPANY TELEPHONE NUMBER:

909-587-1820

TRANSPORT EMERGENCY TELEPHONE NUMBER

909-227-2034

MEDICAL EMERGENCY TELEPHONE NUMBER

909-227-2034

SECTION 2: COMPOSITION, INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS 1% OR GREATER CARCINOGENS 0.1% OR GREATER (SPECIFIC CHEMICAL IDENTITY: COMMON NAME (S)	%(WT./VOL.) (OPTIONAL)	CAS	OTHER LIMITS RECOMMENDED PEL TLVS			
NONE			N/A	N/A	N/A	N/A

**POLYURETHANE ELASTOMERS ARE FULLY REACTED POLYMERS FORMING ARTICLES WHICH ARE NOT
 CONSIDERED HAZARDOUS UNDER OSHA'S CRITERIA 29 CFR 1910.1200. HOWEVER, HAZARDOUS DUSTS, VAPORS,
 GASES, OR FUMES MAY BE RELEASED BY MECHANICAL OR THERMAL PROCESSING, OR BY THERMAL
 DECOMPOSITION.**